

· TYPE _____ · DATE _____ · PROJECT _____

CEL

Sage Celeste — Indoor Steel LED Remote Head

Indoor Steel LED Remote Head

single or double head · 6 V 5.3 W heads · central battery

SUGGESTED SPECIFICATION

Install Sage Celeste indoor steel LED remote heads with long lasting, efficient, ultra bright white LED lamp heads, 6 V 5.3 W per head, adjustable for increased center-to-center spacing, with a chrome-plated metallized reflector and glass lens for optimal light distribution. The housing shall be durable 20-gauge steel in white or black, suitable for wall or ceiling mount, with a universal mounting base for a single-gang switch box. Heads shall be powered from the Sage central battery over the low voltage branch circuit, or from a Sage exit or combo unit with remote capacity, with the maximum run set by system voltage, wire gauge and the total wattage on the run. Heads shall be UL listed with the Sage system and meet UL 924, NFPA 101, NEC, OSHA and local and state codes.

ELECTRICAL SPECIFICATIONS

Low voltage operation from the Sage central battery over the low voltage branch circuit (CB), or from a Sage exit or combo unit with remote capacity (RB); low voltage wiring not provided. Heads are 6 V 5.3 W each. The maximum run is determined by the system voltage, the wire gauge and the total wattage on the run.

LOAD BY CONFIGURATION

Configuration	Load
Single head	5.3 W
Double head	10.6 W

6 V 5.3 W lamp heads. Cabinet sizing and run length per the Sage design.

PRODUCT DATA · INPUT

Operation	CB · central battery · RB · from the host exit or combo
Heads	6 V · 5.3 W each · 1 single · 2 double
Optics	chrome-plated metallized reflector · glass lens
Housing	20-gauge steel · white or black
Mount	wall or ceiling · single-gang switch box

FEATURES

- Long lasting, efficient, ultra bright white LED lamp heads, 6 V 5.3 W, adjustable for center-to-center spacing
- Chrome-plated metallized reflector and glass lens for optimal light distribution
- Durable 20-gauge steel housing, white or black finish
- Universal mounting base to a single-gang switch box; wall or ceiling mount
- Powered from the Sage central battery or a Sage exit or combo unit over low voltage wiring

ORDERING INFORMATION

Operation	CB = powered from the Sage central battery · RB = powered from the host exit or combo unit
Lamp Heads	1 single · 2 double
Housing Color	(blank) White · B Black

Ordering Example: CEL-CB-2

UL CONDITIONS OF ACCEPTABILITY

UL listed with the Sage system products. Meets UL 924, NFPA 101 Life Safety Code, NEC, OSHA, and local and state codes.

NOTE: Refer to the host unit's specification sheet to confirm remote load capacity (RB).

NOTE: Five-year total customer satisfaction warranty.

“Engineered for the spaces it protects.”