

EVE

Universal Back, End or Top Mount

Installation Instructions

Self-luminous — no electrical connections

A) UNIVERSAL BACK, END OR TOP MOUNT — SINGLE & DOUBLE FACE SIGNS

BACK MOUNT

Select arrows as required by removing the arrow insert(s) in the stencil face sheet legend. Remove the plastic protector from the window; discard the angle bracket. Ensure the mounting surface is flat, with no raised areas that may penetrate the sign or cause bending. Use the sign to mark the mounting points, and mount the sign in position using maximum size 8 screws; up to six screws may be used (mounting screws supplied by the installer).

LEGEND & WINDOW REPLACEMENT

Replace the legend and window. The window snaps into the housing by locating tabs at six points: place it into position by locating the two bottom tabs, bend the window outwards slightly at the sides to insert the side tabs, then insert the two tabs along the top edge by flexing the thermoplastic wall or with a ¼" screwdriver, twisting to insert the tabs. To remove the window, insert a flat screwdriver into the slots provided and twist to release the tabs at the two points on the top edge, then flex the window to remove.

TOP OR END MOUNT — UNIVERSAL BRACKET

Select the open holes (not the tapped holes), place the bracket in the mount position and mark the screw anchor locations on the ceiling or wall surface. Install the screw anchors, and install the bracket. Attach the sign to the bracket using the two #8-32 Allen head screws with lock washers provided.

"Engineered for the spaces it protects."

EVE

Canopy, Top or End Mount

Installation Instructions

Model EVE

B) CANOPY, TOP, OR END MOUNT

1. Assemble the angle bracket to the canopy plate using two #8-32 x 1/2" screws, nuts and washers.
2. If mounting direct to a wall or ceiling, use the canopy plate holes to mark the screw anchor and 3/8" clearance hole positions, drill and insert anchors; the canopy location is 2 3/4" x 4" on the drill pattern.
3. Mount the canopy plate to the selected location using the screws supplied (#8-32 x 1" screws to the surface or box).
4. Assemble the sign to the bracket using the two #8 screws provided; select the arrows and replace the legend and window as on page 1.

SAVE THESE INSTRUCTIONS

"Engineered for the spaces it protects."