

· TYPE _____ · DATE _____ · PROJECT _____

MIS

Sage Mist — Indoor High Performance MR16 LED Remote Head

Indoor High Performance MR16 LED Remote Head

single or double head · 3.6 W or 7.0 W per head · central battery

SUGGESTED SPECIFICATION

Install Sage Mist indoor LED remote heads with long lasting, efficient, ultra bright white adjustable LED lamp heads, 3.6 W per head, or 7.0 W high performance MR-16 base LED heads (HL) for premium center-to-center spacing, in an injection-molded, engineering grade 5VA flame-retardant, high-impact thermoplastic housing, white. A universal mounting base plate with hardware shall be included for wall or ceiling mount. Heads shall operate as remote devices on the Sage central battery system over the low voltage run, or from a Sage exit or combo unit with remote capacity, with low voltage wiring by the installer; the maximum run is determined by the system voltage, the wire gauge and the total wattage on the run. Heads shall be UL Listed for damp locations and meet UL 924, NFPA 101, NEC, OSHA and local and state codes.

ELECTRICAL SPECIFICATIONS

Low voltage operation from the Sage central battery over the low voltage run (CB), or from a Sage exit or combo unit with remote capacity (RB); low voltage wiring not provided. The maximum run is determined by the system voltage, the wire gauge and the total wattage on the run; cabinet sizing and run length per the Sage design. Load 3.6 W per head (7.2 W double), or 7.0 W per head with the HL heads (14.0 W double).

LOAD BY CONFIGURATION

Configuration	Load
Single head, standard	3.6 W
Single head, HL	7.0 W
Double head, standard	7.2 W
Double head, HL	14.0 W

Cabinet sizing and run length per the Sage design; refer to the host unit's specification sheet to confirm remote load capacity (RB).

PRODUCT DATA · INPUT

Operation	CB · central battery · RB · from the host exit or combo
Load	3.6 W per head · 7.0 W per head (HL)
Heads	1 single · 2 double, adjustable
Housing	5VA thermoplastic · white
Mount	universal base plate with hardware · wall or ceiling

FEATURES

- Long lasting, efficient, ultra bright white LED lamp heads; adjustable 3.6 W heads increase center-to-center spacing
- HL option: 7.0 W high performance MR-16 base LED lamps for premium center-to-center spacing
- Injection-molded, engineering grade 5VA flame retardant, high-impact thermoplastic; white
- Universal mounting base plate included with mounting hardware; wall or ceiling mount
- UL Listed for damp locations; meets UL 924, NFPA 101, NEC and OSHA
- Powered from the Sage central battery or a Sage exit or combo unit over low voltage wiring

TEMPERATURE

Operating Temperature 0 to 50 °C (UL damp location)

ORDERING INFORMATION

Operation	CB = powered from the Sage central battery · RB = powered from the host exit or combo unit
Lamp Heads	1 single · 2 double
Housing Color	White
Options	(blank) 3.6 W heads · HL = 7.0 W high performance heads
Ordering Example: MIS-CB-2-HL	

UL CONDITIONS OF ACCEPTABILITY

UL Listed for damp locations (0 to 50 °C). Meets UL 924, NFPA 101 Life Safety Code, NEC, OSHA, and local and state codes.

NOTE: Refer to the host unit's specification sheet to confirm remote load capacity (RB).

NOTE: Five-year total customer satisfaction warranty.

“Engineered for the spaces it protects.”