

· TYPE _____ · DATE _____ · PROJECT _____

SOA

Sage Solace — Mini Indoor LED Remote Head

Mini Indoor LED Remote Head

single or double head · 0.5 W per head · central battery

SUGGESTED SPECIFICATION

Install Sage Solace mini indoor LED remote heads with long lasting, efficient, ultra bright white LED lamp heads, one 0.5 W LED per head, in a unique all-inclusive lamp, diffuser and lens assembly on adjustable heads for center-to-center spacing, in an injection-molded, engineering grade 5VA flame-retardant, high-impact thermoplastic housing, white or black. A universal mounting adapter plate with mounting hardware shall be included for wall or ceiling mount. Heads shall operate as remote devices on the Sage central battery system over the low voltage run, or from a Sage exit or combo unit with remote capacity, with low voltage wiring by the installer; the maximum run is determined by the system voltage, the wire gauge and the total wattage on the run. Heads shall meet UL 924, NFPA 101, NEC, OSHA and local and state codes.

ELECTRICAL SPECIFICATIONS

Low voltage operation from the Sage central battery over the low voltage run (CB), or from a Sage exit or combo unit with remote capacity (RB); low voltage wiring not provided. The maximum run is determined by the system voltage, the wire gauge and the total wattage on the run; cabinet sizing and run length per the Sage design. Load 0.5 W per head, 1.0 W double.

LOAD BY CONFIGURATION

Configuration	Load
Single head	0.5 W
Double head	1.0 W

One 0.5 W white LED per head. Cabinet sizing and run length per the Sage design; refer to the host unit's specification sheet to confirm remote load capacity (RB).

PRODUCT DATA · INPUT

Operation	CB · central battery · RB · from the host exit or combo
Load	0.5 W per head · 1.0 W double
Heads	1 single · 2 double, adjustable
Housing	5VA thermoplastic · white or black
Mount	universal adapter plate with hardware · wall or ceiling

FEATURES

- Long lasting, efficient, ultra bright white LED lamp heads, one 0.5 W LED per head
- Unique all-inclusive lamp, diffuser and lens assembly; adjustable heads for center-to-center spacing
- Injection-molded, engineering grade 5VA flame retardant, high-impact thermoplastic; white or black
- Universal mounting adapter plate included with mounting hardware; wall or ceiling mount
- Meets UL 924, NFPA 101, NEC and OSHA
- Powered from the Sage central battery or a Sage exit or combo unit over low voltage wiring

ORDERING INFORMATION

Operation	CB = powered from the Sage central battery · RB = powered from the host exit or combo unit
Lamp Heads	1 single · 2 double
Housing Color	(blank) White · B Black

Ordering Example: SOA-CB-2-B

UL CONDITIONS OF ACCEPTABILITY

Meets UL 924, NFPA 101 Life Safety Code, NEC, OSHA, and local and state codes.

NOTE: Refer to the host unit's specification sheet to confirm remote load capacity (RB).

NOTE: Five-year total customer satisfaction warranty.

“Engineered for the spaces it protects.”