

· TYPE _____ · DATE _____ · PROJECT _____

SOL

Sage Solara — LED Outdoor Polycarbonate Remote Head

LED Outdoor Polycarbonate Remote Head

single or double head · 0.5 W per head · wet location · central battery

SUGGESTED SPECIFICATION

Install Sage Solara outdoor LED remote heads with long lasting, efficient, ultra bright white LED lamp heads, 0.5 W per head, in a unique all-inclusive lamp, diffuser and lens assembly on adjustable heads for center-to-center spacing, in a sealed and gasketed, engineering grade, high-impact polycarbonate housing, gray or black. A universal mounting adapter plate shall be included for a single-gang switch box, wall or ceiling. Heads shall operate as remote devices on the Sage central battery system over the low voltage run, or from a Sage exit or combo unit with remote capacity, with low voltage wiring by the installer; the maximum run is determined by the system voltage, the wire gauge and the total wattage on the run. Heads shall be UL Listed for wet locations from -30 to 50 °C and meet UL 924, NFPA 101, NEC, OSHA and local and state codes.

ELECTRICAL SPECIFICATIONS

Low voltage operation from the Sage central battery over the low voltage run (CB), or from a Sage exit or combo unit with remote capacity (RB); low voltage wiring not provided. The maximum run is determined by the system voltage, the wire gauge and the total wattage on the run; cabinet sizing and run length per the Sage design. Load 0.5 W per head (1 LED at 0.5 W), 1.0 W double.

LOAD BY CONFIGURATION

Configuration	Load
Single head	0.5 W
Double head	1.0 W

One 0.5 W LED per head. Cabinet sizing and run length per the Sage design; refer to the host unit's specification sheet to confirm remote load capacity (RB).

PRODUCT DATA · INPUT

Operation	CB · central battery · RB · from the host exit or combo
Load	0.5 W per head · 1.0 W double
Heads	1 single · 2 double, adjustable
Housing	sealed and gasketed polycarbonate · gray or black
Mount	single-gang switch box, adapter plate included · wall or ceiling

FEATURES

- Long lasting, efficient, ultra bright white LED lamp heads, 0.5 W per head; all-inclusive lamp, diffuser and lens assembly
- Adjustable heads for center-to-center spacing
- Sealed and gasketed, engineering grade, high-impact polycarbonate housing; gray or black
- Universal mounting adapter plate included; single-gang switch box; wall or ceiling
- UL Listed for wet locations, -30 to 50 °C; meets UL 924, NFPA 101, NEC and OSHA
- Powered from the Sage central battery or a Sage exit or combo unit over low voltage wiring

TEMPERATURE

Operating Temperature -30 to 50 °C (UL wet location)

ORDERING INFORMATION

Operation	CB = powered from the Sage central battery · RB = powered from the host exit or combo unit
Lamp Heads	1 single · 2 double
Housing Color	(blank) Gray · B Black

Ordering Example: SOL-CB-2-B

UL CONDITIONS OF ACCEPTABILITY

UL Listed for wet locations (-30 to 50 °C). Meets UL 924, NFPA 101 Life Safety Code, NEC, OSHA, and local and state codes.

NOTE: Refer to the host unit's specification sheet to confirm remote load capacity (RB).

NOTE: Five-year total customer satisfaction warranty.

“Engineered for the spaces it protects.”