

TYPE _____ · DATE _____ · PROJECT _____

CB COMPATIBLE
 24VDC central battery (RE)

IP66 RATED
 Wet location exterior use

DUAL FUNCTION
 Emergency + night/security

ARCHITECTURAL
 Slim profile, custom finishes

Aspen

ASP

GENERAL DESCRIPTION

Slim exterior architectural emergency luminaire in extruded aluminum. IP66 wet location rated for building facades and over-door applications. Dual function emergency and night/security lighting.

CB compatible (RE) or integral battery (BB).

CONSTRUCTION & OPERATION

Extremely low profile extruded aluminum.

White satin or custom anodized finish.

IP66 wet location listed.


Elongated egress lighting pattern.

BB (integral battery), RE (24VDC central battery), or AC versions.

Universal 120/277VAC.

Dual emergency/night-security function.

UL 924 and NFPA 101 listed.



SPECIFICATIONS

Lamp Life	> 50,000 hours
IP Rating	IP66 — Wet Location
Operation	BB / RE (24VDC CB) / AC
Input	120/277 VAC
Finish	White satin / custom anodized
Listings	UL 924 / NFPA 101

CB COMPATIBLE	SAGE LIVE™ READY
----------------------	-------------------------

ORDERING INFORMATION

Series	Watts	Volts	CODE	OPTION / DESCRIPTION
MAE	10W	120/277VAC	BB	Integral Battery Unit
		24VDC	RE	Remote — Central Battery
		120/277V	AC	AC Supply Remote

Ordering Example: MAE-BB-120



“Engineered for the spaces it protects.”