

TYPE _____ · DATE _____ · PROJECT _____

CB COMPATIBLE
Factory ELC for central battery

DIE-CAST AL
Durable exterior-grade housing

CANOPY READY
Parking structures and entries

DLC LISTED
Utility rebate eligible

Atlas

ATL

GENERAL DESCRIPTION

Die-cast aluminum LED canopy luminaire for covered parking and building entrances. High-output LED in durable exterior-grade housing. Optional factory ELC for Sage central battery emergency code compliance..

CONSTRUCTION & OPERATION


Die-cast aluminum housing, powder coat finish.

Surface mount to flat ceilings.

Universal 120-277VAC with 0-10V dimming.

Optional factory ELC for Sage central battery emergency operation.

cULus listed, DLC listed, RoHS compliant.



SPECIFICATIONS	
Lumen Output	30-60W range
Input	120-277 VAC
Dimming	0-10V standard
Housing	Die-cast aluminum
Mount	Surface / Flush ceiling
Listings	cULus / DLC
<div style="display: flex; justify-content: space-around;"> CB COMPATIBLE SAGE LIVE™ READY </div>	

ORDERING INFORMATION

Series	Watts	Volts	CODE	OPTION / DESCRIPTION
ATL	30-60W	120-277VAC	ELCXX	Emergency Lighting Control

Ordering Example: **CPL-40W-120-ELCXX**



“Engineered for the spaces it protects.”