

· TYPE _____ · DATE _____ · PROJECT _____

ROUND OR SQUARE
Two forms

FIELD-SELECTABLE
Lumen & Kelvin

PATH-READY
Landscape and walkways

5-YEAR WARRANTY
Total customer satisfaction

Atmos

ATM

GENERAL DESCRIPTION

Round and square LED bollards with field-selectable lumen output and color temperature — one SKU, set at install.

CONSTRUCTION & OPERATION

Field selectable 3000K (warm white), 4000K (neutral white), and 5000K (cool white) color temperatures.*

Long-life LEDs provide at least 70% of initial lumen output (L70) for ≥ 163,000 hours of operation, and at least 90% of initial lumen output (L90) for ≥ 50,000 hours of operation.**

LED chromaticity based on ≤ 5-step ANSI quadrangles.

LED color maintenance ≤ 0.003 chromaticity shift ($\Delta u'v'$) over the initial 6,000 hours of operation.



SPECIFICATIONS

LED Life 163,000 hours

Operating Temp -40 °C to 55 °C

Listed to cULus (Wet); DLC Premium; IP65

cULus WET LISTED

DLC PREMIUM

ORDERING INFORMATION

Series	Nominal Lumen Output	Select	Housing
ATM	3L – 3,000 lm	LKFS – Lumen/Kelvin selectable	BLK – Black
	2L – 2,000 lm		Blank – Bronze

Ordering Example: ATM-R-3L-LKFS-BLK

LISTED TO



“Engineered for the spaces it protects.”