

TYPE _____ · DATE _____ · PROJECT _____

CB COMPATIBLE
Factory ELC for central battery

HIGH EFFICACY
Up to 151 lm/W

IP65 RATED
Full ingress protection

LONG LIFE
L70 > 158,000 hours

Basalt

BAS

GENERAL DESCRIPTION

Heavy-duty cast aluminum LED wall pack with forward-throw distribution. Selectable 4000K/5000K CCT. Universal 120-277VAC with optional emergency lighting control for Sage central battery compliance..

CONSTRUCTION & OPERATION

Cast aluminum housing, dark bronze powder coat, glass lens.

IP65 rated.

Universal 120-277VAC with 4000K or 5000K CCT.

0-10V dimming.

Optional factory ELC for Sage central battery emergency operation.

cULus wet listed.

L70 > 158,000 hours.



SPECIFICATIONS	
Lumen Output	6,401 to 15,738 lm
Efficacy	141 to 151 lm/W
CCT	4000K / 5000K
Input	120-277 VAC
Lamp Life	L70 > 158,000 hours
Listings	cULus / IP65 / Wet
<div style="display: flex; justify-content: space-around;"> CB COMPATIBLE SAGE LIVE™ READY </div>	

ORDERING INFORMATION

Series	Watts	Volts	CODE	OPTION / DESCRIPTION
BAS	26-78W	120-277VAC	4000K	4000K CCT
			5000K	5000K CCT
			ELCXX	Emergency Lighting Control

Ordering Example: **WPT-40W-120-5000K-ELCXX**



“Engineered for the spaces it protects.”