

· TYPE _____ · DATE _____ · PROJECT _____

UNIVERSAL MOUNT
Wall, top, or end

RED OR GREEN
Field choice

LONG-LIFE LED
Efficient and bright

DAMP RATED
Wet/damp location listed

Birch

BIR

GENERAL DESCRIPTION

An ultra-bright, energy-efficient, long-life red or green LED exit sign in injection-molded engineering-grade thermoplastic — wall, top, or end mountable via a universal knockout pattern.

CONSTRUCTION & OPERATION

Ultra-bright, energy efficient, long-life Red or Green LED EXIT sign illumination.

Selectable Red/Green (RG) version available. See ordering matrix below.

Mounting canopy included for top or end mount.

Universal knockout pattern on back plate for wall mount.



SPECIFICATIONS

Input Power	Dual 120/277 voltage
Operation	BB · NB · REC · REP
Operating Temp	0 °C to 50 °C
Warranty	Five year warranty
Listed to UL 924, NFPA 101; DAMP	

DAMP RATED

SELF-DIAGNOSTIC

ORDERING INFORMATION

Series	Operation	Faces	Letter	Housing
BIR	BB – Battery Backup	2 – Universal Single/Double Face	R – Red	W – White
	NB – No Battery (AC)		G – Green	B – Black
	REC – Remote / Central		RG – Red/Green (field selectable)	
	REP – Remote DC / POE			

Ordering Example: BIR-BB-2-RG-W-SDT

Options: SDT Self-Diagnostics (not available with RG · 48 48V DC input (available only with REP units) · 60 60V DC input (available only with REP units) · USA Assembled in the USA

1: RG (Red/Green) letter color is field selectable. 2: SDT (Self-Diagnostics) not available with RG units.

LISTED TO



UL 924 / NFPA 101

ASSEMBLED IN USA



Per Buy American Act

“Engineered for the spaces it protects.”