

· TYPE _____ · DATE _____ · PROJECT _____

DIE-CAST
Solid aluminum housing

THIN PROFILE
Slim on the wall

LONG-LIFE LED
Efficient, durable

DAMP RATED
Wet/damp location listed

Cairn

CAI

GENERAL DESCRIPTION

A thin die-cast aluminum exit sign — a slim, durable metal housing for a premium look that endures.

CONSTRUCTION & OPERATION

Ultra bright, energy efficient, long life Red or Green LEDs.

Premium-grade, die-cast aluminum housing (also available in optional black or white powder-coated finishes).

Field selectable knockout Chevron directional indicators.

Quick-snap face plate closure.



SPECIFICATIONS

Input Power	Universal Input 120/277VAC
Operation	BB · NB · REC · REP
Operating Temp	0 °C to 50 °C
Housing	Premium-grade, die-cast aluminum
Warranty	Five year warranty
Listed to UL 924, NFPA 101; cETLus (Intertek); DAMP	

DAMP RATED


UL 924 LISTED

ORDERING INFORMATION

Series	Operation	Faces	Letter	Housing
CAI	BB – Battery Backup	1 – Single	R – Red	W – White
	NB – No Battery (AC)	2 – Double	G – Green	B – Black
	REC – Remote / Central			A – Aluminum
	REP – Remote DC / POE			WG – Wire Guard

Ordering Example: CAI-BB-1-R-G-W-WG

Options: 48 48VDC input (REP Operation) · 60 60VDC input (REP Operation) · WG Wire Guard · VS Vandal Shields · PF1 Polycarbonate Face — Single Face · PF2 Polycarbonate Face — Double Face



“Engineered for the spaces it protects.”