

· TYPE _____ · DATE _____ · PROJECT _____


RECESSED
Hidden until needed


INTEGRAL BATTERY
90-minute egress


AUTOMATIC
On at power loss


DAMP RATED
Wet/damp location listed

Canopy

CAN

GENERAL DESCRIPTION

A recessed LED emergency unit with an integral battery — concealed in the ceiling, it delivers egress light the moment power fails.

CONSTRUCTION & OPERATION

Ultra-bright, energy efficient, long-life White LED adjustable lamp heads provide up to 50-ft center-to-center spacing with a 3-ft path of egress at 12-ft mounting height.

1.0 watt (1 LED x 1.0 watt) per head.

Unique all-inclusive lamp, reflector, and lens assembly.

Injection-molded, engineering grade, 5VA flame retardant, impact-resistant, thermoplastic in white or black finish.



SPECIFICATIONS

Input Power	120/277 VAC; 24 VDC remote
Operating Temp	10 °C – 40 °C
Housing	Injection-molded, engineering grade
Warranty	Five-year warranty
Listed to UL 924, NFPA 101; DAMP	

DAMP RATED

SELF-DIAGNOSTIC

ORDERING INFORMATION

Series	Housing
CAN	W – White
	B – Black

Ordering Example: CAN-W

Options: SDT Self-Diagnostics

LISTED TO



UL 924 / NFPA 101

“Engineered for the spaces it protects.”