

· TYPE _____ · DATE _____ · PROJECT _____

ALUMINUM
Durable, premium housing

EDGE-LIT
Uniform illumination

CLEAN LINES
Architectural profile

DAMP RATED
Wet/damp location listed

Citrine

CIT

GENERAL DESCRIPTION

An edge-lit aluminum exit sign with a durable housing and a uniformly illuminated acrylic panel — a premium look that holds up.

CONSTRUCTION & OPERATION

Ultra bright, energy efficient, long life Red or Green LEDs.

UV-stabilized ultra-clear acrylic edgelit panel provides consistent, uniform illumination.

Double face utilizes factory installed silver or white mylar background panel.

4.8V long life, maintenance-free, rechargeable NiCd (self-contained, BB / 120-277VAC-with-battery models only).



SPECIFICATIONS

Input Power	Universal Input 120/277VAC
Operation	BB · NB · REC
Operating Temp	0 °C to +50 °C
Housing	Premium-grade, extruded aluminum
Listed to UL 924, NFPA 101; DAMP	

DAMP RATED

SELF-DIAGNOSTIC

ORDERING INFORMATION

Series	Operation	Faces	Letter	Housing	Panel
CIT	BB – Battery Backup	1 – Single	R – Red	W – White	C – Clear (footnote 5: available with single face only)
	NB – No Battery (AC)	2 – Double	G – Green	B – Black	M – Mirror
	REC – Remote / Central			A – Aluminum	W – White

Ordering Example: CIT-BB-1-R-W-C-2C

Options: DG Self-Test Diagnostics (footnote 1: BB · 48 12-48VDC input (footnote 2: REC models) · 60 12-60VDC input (footnote 2: REC models) · CUSTOM Custom Wording · USA

Assembled in USA · 2C Dual Circuit Operation (footnote 3: · SPV 208/220/240 Volt, 50/60Hz (footnote 4: not

1 — BB models. 2 — REC models.

LISTED TO



UL 924 / NFPA 101

ASSEMBLED IN USA



Per Buy American Act

“Engineered for the spaces it protects.”