

· TYPE _____ · DATE _____ · PROJECT _____

LINEAR EGRESS
Emergency + night lighting in one run

SELF-TEST
Automatic diagnostics on BB models

OUTDOOR-RATED
Built for the building's edges

SAGE LIVE™
Monitored on the central battery

Comet

CMT

GENERAL DESCRIPTION

A linear LED outdoor egress luminaire with emergency and night lighting, plus automatic self-test on battery-backup models. Part of the Sage central battery system, monitored through Sage Live.


CONSTRUCTION & OPERATION

Very low profile extruded aluminum housing and mount bracket blend seamlessly with structural metal frames.

Custom satin finishes for extended outdoor use are available to match any surface.

Available in Top or Wall mount.

Remote power supply for BB & AC models.



SPECIFICATIONS

Operation	BB · AC · RE
Operating Temp	0 °C to 50 °C
Housing	2"
Warranty	10 year warranty

Listed to UL 924, NFPA 101; cETLus (Intertek); BABA; BAA; WET

SELF-DIAGNOSTIC

UL 924 LISTED

ORDERING INFORMATION

Series	Operation	Power	Housing	Mount
CMT	BB – Battery Backup	10 – 10 watts emergency and normal power	W – Satin White	T – Top
	AC – No Battery	20 – 20 watts emergency and normal power	K – Black	W – Wall
	RE – 24V Remote (central battery)		A – Aluminum	
			B – Dark Bronze	
			X – Custom	

Ordering Example: CMT-BB-20-A-W-SD

Options: DAC Dual AC Input · SD Night Lighting (BB-20 Models only)** — ** · REC Sage remote power supply Recessed Mount · 2EM 2 Hours Run Time (BB-20 Models only) · 5HT 5" Canopy Height · CW1 3800K · CW2 3200K · CW3 2900K

LISTED TO



ASSEMBLED IN USA



Per Buy American Act

“Engineered for the spaces it protects.”