

· TYPE _____ · DATE _____ · PROJECT _____

CORROSION-RESISTANT
Enclosed for harsh areas

TWO ADJUSTABLE HEADS
Aim both ways

CENTRAL-BATTERY
Low-voltage powered

5-YEAR WARRANTY
Total customer satisfaction

Compass

COM

GENERAL DESCRIPTION

An enclosed, corrosion-resistant LED remote head with two fully adjustable ultra-bright 3.3 W heads, powered from the central battery over low-voltage wiring.

CONSTRUCTION & OPERATION

Two fully adjustable, ultra bright 3.3 watt high performance MR-16 base LED lamp heads for optimized center-to-center spacing..

Powered from low voltage 6V/12V DC power source with low voltage wiring (not provided).

Housing is reinforced polycarbonate construction in white or black finish.

Corrosion-resistant enclosure with one piece, high-impact resistant, UV stabilized polycarbonate lens and molded gasket with stainless steel screws.



SPECIFICATIONS

Input Power	Low voltage 6V / 12V DC power source
Operation	RB · RE
Operating Temp	0 °C to 50 °C
Warranty	5 year warranty
Listed to UL 924, NFPA 101; cULus (Wet)	

UL 924 LISTED

cULus WET LISTED

ORDERING INFORMATION

Series	Operation	Lamp Heads	Color
COM	RB – Powered from Sage emergency or Sage emergency	1 – Single Head	W – White
	RE – Powered from Central Battery System	2 – Double Head	B – Black

Ordering Example: COM-RB-2-B-TP

Options: TP Tamper-proof

LISTED TO



UL 924 / NFPA 101

“Engineered for the spaces it protects.”