

· TYPE _____ · DATE _____ · PROJECT _____

CHICAGO-APPROVED
Meets the jurisdiction

EXIT / STAIR
Both faces covered

UV-STABLE ACRYLIC
Consistent over time

DAMP RATED
Wet/damp location listed

Cosmos

COS

GENERAL DESCRIPTION

A Chicago-approved edge-lit aluminum exit/stair sign with UV-stabilized, silk-screened acrylic panels for consistent, uniform illumination from ultra-bright, efficient LEDs.

CONSTRUCTION & OPERATION

Ultra-bright, energy efficient, long-lasting white LEDs provide uniform illumination.

UV stabilized, silk screened acrylic panels provide consistent, uniform illumination.

Die-cast aluminum mounting canopy provided for universal top, end or back mount.

Premium-grade, extruded aluminum housing (also available in optional white powder-coated finish).



SPECIFICATIONS

Input Power	Dual 120V/277V voltage
Operation	BB · AC · RE
Operating Temp	0 °C to 50 °C
Warranty	Five year warranty
Listed to UL 924, NFPA 101; cETLus (Intertek); DAMP	

DAMP RATED

UL 924 LISTED

ORDERING INFORMATION

Series	Operation	Faces	Letter	Housing	Signage / Directional Arrows
COS	BB – Battery Backup	1 – Single Face	RW – Red On White	A – Aluminum	-NA – Exit None
	AC – AC Only	2 – Universal Single/Double		W – White	-S-NA – Stair None
	RE – Remote (central battery)				-DA – Exit Double
					-S-DA – Stair Double
					-RA(1) – Exit Right
					-S-RA(1) – Stair Right
					-LA(1) – Exit Left
					-S-LA(1) – Stair Left
					-LARA(2) – Exit Left/Right
					-S-LARA(2) – Stair Left/Right

Ordering Example: COS-BB-2-RW-A-DA

(1) Available in single face configuration only. (2) Available in double face configuration only.

LISTED TO



“Engineered for the spaces it protects.”