

TYPE \_\_\_\_\_ · DATE \_\_\_\_\_ · PROJECT \_\_\_\_\_

**EXIT + EMERGENCY**  
Low-profile recessed combo

**CB COMPATIBLE**  
24VDC central battery (REC)

**ADJUSTABLE LIGHT**  
Downlight angle optimizable

**SELF-DIAGNOSTICS**  
Optional DG auto-test

# Cove

COV


## GENERAL DESCRIPTION

Low-profile recessed combination exit sign and emergency unit for architectural finished ceilings. Universal single/double face with adjustable LED downlight. 120/277VAC with integral battery or 24VDC central battery operation.

Optional self-test diagnostics and custom wording available.

## CONSTRUCTION & OPERATION

- Engineering grade thermoplastic housing in white or black.
- Universal single/double face with EZ snap-out chevron indicators.
- Adjustable LED downlight and EZ-snap mounting canopy.
- Universal 120/277VAC with NiCd battery for 90-minute operation (BB).
- Central battery operation: 24VDC (REC).
- Optional DG self-test diagnostics.
- UL Listed per UL Standard 924, NFPA 101, and Title 20.



SPECIFICATIONS	
<b>Input (AC)</b>	120/277 VAC (Universal)
<b>Battery</b>	NiCd, maintenance-free (BB)
<b>Duration</b>	90 min. minimum
<b>Face Config.</b>	Universal Single/Double
<b>DC Operation</b>	24VDC (REC) / 60VDC (POE)
<b>Listings</b>	UL 924 / NFPA 101 / Title 20
<span style="margin-right: 50px;"><b>CB COMPATIBLE</b></span> <span><b>SAGE LIVE™ READY</b></span>	

## ORDERING INFORMATION

Series	Watts	Volts	CODE	OPTION / DESCRIPTION
COV			BB	120/277VAC with Battery
			REC	Central Battery
			U	Universal Single/Double Face
			R	Red Letter Color
			G	Green Letter Color
			W	White Housing
			B	Black Housing
			DG	Self-Test Diagnostics
			48	48VDC Input
			60	60VDC Input
			CUSTOM	Custom Wording

**Ordering Example: CLP-BB-R-W-U**



*“Engineered for the spaces it protects.”*