

· TYPE _____ · DATE _____ · PROJECT _____

UP / DOWN
Switch at the fixture

ARCHITECTURAL
Clean cylinder form

LED
Efficient, long-life

5-YEAR WARRANTY
Total customer satisfaction

Delta

DEL

GENERAL DESCRIPTION

An up/down cylinder luminaire — select down-only or up/down via an internal switch. A clean architectural form for entries, lobbies, and exteriors.

CONSTRUCTION & OPERATION

Available in 3000k (warm white), 4000k (neutral white), and 5000k (cool white) color temperatures.*

Long-life LEDs provide up to 153,000 hours of operation with at least 70% of initial lumen output (L70).**

DEL-UPDN provides a range of 2,446 to 2,509 nominal lumens and 82 lumens per watt (lm/W).*

Internal switch allows a choice of down light or up/down light.



SPECIFICATIONS

Light Output	2,509
LED Life	153,000 hours
Operating Temp	0 °C to 50 °C
Housing	Aluminum
Listed to cETLus (Intertek); WET	

ENERGY STAR

WET LOCATION

ORDERING INFORMATION

Series	Nominal Lumen Output	CCT	Voltage
DEL	2L – 2,000 lumens	3K – 3000k	120V – 120 Volts
		4K – 4000k	
		5K – 5000k	

Ordering Example: DEL-UPDN-2L-3K-120V

LISTED TO



UL 924 / NFPA 101

“Engineered for the spaces it protects.”