

· TYPE _____ · DATE _____ · PROJECT _____

NYC-READY
Meets New York City

DIE-CAST
Solid aluminum housing

FIELD-SET
Configurable on site

5-YEAR WARRANTY
Total customer satisfaction

Drift

DRI

GENERAL DESCRIPTION

A New York City die-cast aluminum exit sign — durable metal construction, field-adjustable, built to the jurisdiction. (ST description pending — drafted from spec; confirm before lock.)

CONSTRUCTION & OPERATION

Adjustable, glare-free PAR-Type lamp heads with 9W (on 6V models) and 12W (on 12V models) incandescent lamps.

Field installable third lamp head included with the 27W and 50W models.

Durable powder-coated 20-gauge steel construction in white or black finish.

Injection-molded engineering grade high-impact thermoplastic heads.



SPECIFICATIONS

Input Power	120/277 VAC; 24 VDC remote
Operating Temp	0 °C to 50 °C
Housing	Durable powder-coated 20-gauge steel
Warranty	Five year warranty
Listed to UL 924, NFPA 101; cETLus (Intertek)	

UL 924 LISTED


LOW LOAD

ORDERING INFORMATION

Series	Voltage	No. Of Heads	Unit Watts	Lamp Watts	Color
DRI	6 – 6 Volt	2 – 2 Heads	18 – 18 Watts (note 1)	9 – 9 Watts (note 1)	(blank) – White
	12 – 12 Volt	3 – 3 Heads	27 – 27 Watts (note 1)	12 – 12 Watts (note 2)	B – Black
			50 – 50 Watts (note 2)		

Ordering Example: DRI-6-2-18-9

1 Available in 6V units only. 2 Available in 12V units only.



“Engineered for the spaces it protects.”