

· TYPE _____ · DATE _____ · PROJECT _____

HAZ-LOC RATED
For classified areas

ADJUSTABLE HEADS
Aim the egress light

CENTRAL-BATTERY
Low-voltage powered

5-YEAR WARRANTY
Total customer satisfaction

Echo

ECH

GENERAL DESCRIPTION

A hazardous-location LED remote head with adjustable lamp heads, powered from the central battery over low-voltage wiring — egress lighting for classified areas.

CONSTRUCTION & OPERATION

Two fully adjustable, ultra bright 3.3 watt high performance kept base LED lamp heads for optimized center-to-center spacing.

Powered from low voltage 6V/12V DC power source with low voltage wiring (not provided).

Housing is fiberglass reinforced construction in gray finish.

Corrosion-resistant enclosure with one piece, high-impact resistant, UV stabilized polycarbonate lens and molded gasket with stainless steel screws.



SPECIFICATIONS

Input Power	120/277 VAC; 24 VDC remote
Operation	RB · RE
Operating Temp	0 °C to 50 °C
Housing	Fiberglass reinforced housing, gray
Warranty	5 year warranty
Listed to UL 924, NFPA 101; WET	

UL 924 LISTED

WET LOCATION

ORDERING INFORMATION

Series	Operation	Lamp Heads	Color
ECH	RB – Powered from EBU or EXIT Combo	1 – Single Head	G – Gray
	RE – Powered from Central Battery System	2 – Double Head	

Ordering Example: ECH-RB-2-G-TP

Options: TP Tamper-proof

LISTED TO



UL 924 / NFPA 101

“Engineered for the spaces it protects.”