

TYPE \_\_\_\_\_ · DATE \_\_\_\_\_ · PROJECT \_\_\_\_\_

**CB COMPATIBLE**  
10W, 13W, or 25W emergency driver

**IP65 RATED**  
Full ingress protection

**SELECTABLE CCT**  
4000K or 5000K field selectable

**DLC 5.1 PREMIUM**  
Utility rebate eligible

# Ember

EMB

## GENERAL DESCRIPTION

Full cut-off LED wall pack in cast aluminum with IP65 protection. Selectable lumen output and 4000K/5000K CCT. Optional 347-480V input.

Factory-installed ELC available for Sage central battery emergency operation.

## CONSTRUCTION & OPERATION

Cast aluminum with dark bronze powder coat finish, glass lens, IP65 rated.

Selectable lumen output and 4000K/5000K CCT.

Universal 120-277VAC or optional 347-480VAC.


0-10V dimming.

Factory ELC with 10W, 13W, or 25W emergency driver.

cULus wet listed.

L70 > 123,000 hours.

DLC 5.1 premium.



SPECIFICATIONS	
<b>Lumen Output</b>	9L / 17L / 36L / 60L (selectable)
<b>CCT</b>	4000K / 5000K (selectable)
<b>Input</b>	120-277 VAC / 347-480V (UNC)
<b>Housing</b>	Cast aluminum, IP65
<b>Lamp Life</b>	L70 > 123,000 hours
<b>Listings</b>	cULus / DLC 5.1 / Wet / IP65
<div style="display: flex; justify-content: space-around;"> <span>CB COMPATIBLE</span> <span>SAGE LIVE™ READY</span> </div>	

## ORDERING INFORMATION

Series	Watts	Volts	CODE	OPTION / DESCRIPTION
EMB	9L/17L/36L/60L	120-277V	SK	4000K/5000K Selectable CCT
		347-480V	UNC	347-480V Input
			ELCXX	Emergency Lighting Control
			EM10	10W Emergency Driver
			EM13	13W Emergency Driver
			EM25	25W Emergency Driver

Ordering Example: **WPF-9L-120-SK-EM10**



*“Engineered for the spaces it protects.”*