

· TYPE _____ · DATE _____ · PROJECT _____

SELF-LUMINOUS
Tritium-lit, always on

NO POWER
No wiring, no battery

NO TESTING
Legally exempt from monitoring

BAA CERTIFIED
Assembled in the USA

Evergreen

EVE

GENERAL DESCRIPTION

Self-luminous (radioluminescent) exit signs, internally illuminated by sealed tritium gas — no wiring, no battery, and legally exempt from the monitoring and testing other exits require. In a Sage building, the exits take care of themselves so Sage Live watches the rest.

CONSTRUCTION & OPERATION

One-piece flameproof thermoplastic injection-molded housing, only 1" thick.

Universal field-adjustable chevron arrows and universal mounting brackets.

Standard finishes: satin white or black housing, with white lettering and high-contrast red, green, or black faceplate. Optional finishes include custom colors.

No visible mounting hardware.



SPECIFICATIONS

Input Power 120/277 VAC; 24 VDC remote

Operating Temp 0 °C to 50 °C

Listed to UL 924, NFPA 101; cETLus (Intertek)

UL 924 LISTED

NO LOAD

ORDERING INFORMATION

Series	Useful Life	Faces	Face Color	Housing
EVE	10 – 10 YRS	1 – 1	R – RED	W – WHITE
	20 – 20 YRS	2 – 2	G – GREEN	B – BLACK
			"COLOR" – CUSTOM COLOR	"COLOR" – CUSTOM FINISH

Ordering Example: EVE-10-1-R-W

LISTED TO



UL 924 / NFPA 101

ASSEMBLED IN USA



Per Buy American Act

“Engineered for the spaces it protects.”