

· TYPE _____ · DATE _____ · PROJECT _____

WET-LOCATION
Sealed for moisture

SEMI-RECESSED
Low profile

INTEGRAL BATTERY
90-minute egress

DAMP RATED
Wet/damp location listed

Falls

FLS

GENERAL DESCRIPTION

A wet-location semi-recessed LED MR16 emergency unit with an integral battery — sealed egress lighting for damp and wet spaces.

CONSTRUCTION & OPERATION

Two fully adjustable semi-recessed, round 7-watts LED MR16 lamp heads for optimal light distribution.

Ultra-bright, energy efficient, long-life White LED lamps provide up to 76-ft center-to-center spacing with 3-ft path of egress at 7.5-ft mounting height.

Injection-molded, engineering grade, 5VA flame retardant, high-impact resistant, thermoplastic in gray or black finish.

Fully gasketed clear polycarbonate cover offers protection against wet, non-hazardous dust, corrosive atmospheres and to water spray or splashing water locations.



SPECIFICATIONS

Input Power	120/277 VAC; 24 VDC remote
Operation	BB
Operating Temp	0 °C to 50 °C
Warranty	5 year warranty

Listed to UL 924, NFPA 101; DAMP; WET

DAMP RATED

SELF-DIAGNOSTIC

ORDERING INFORMATION

Series	Operation	Housing
FLS	BB – Battery Backup	(Blank) – Gray B – Black

Ordering Example: FLS-BB-B-CW

Options: USA Assembled in USA · SDT Self-diagnostics · CW Internal heater with battery blanket · CEC Certified to CEC under Title 20 Regulations

1: Not available with CEC option. Contact for layout assistance.

LISTED TO



UL 924 / NFPA 101

ASSEMBLED IN USA



Per Buy American Act

“Engineered for the spaces it protects.”