

· TYPE _____ · DATE _____ · PROJECT _____

EXIT + EMERGENCY
Both in one unit

HAZ-LOC RATED
Classified areas

ALL LED
Efficient, long-life

SELF-TEST
Diagnostics on battery models

Frontier

FRO

GENERAL DESCRIPTION

An all-LED hazardous-location exit and emergency combo — sealed, rated EXIT plus emergency egress for classified areas.

CONSTRUCTION & OPERATION

Two fully adjustable, ultra bright 3.6 watt high performance MR-16 base LED lamp heads for optimized center-to-center spacing.

Long-life, energy efficient Red or Green LED EXIT sign illumination.

Housing is fiberglass reinforced polycarbonate construction in gray finish.

Corrosion-resistant enclosure with one piece, high-impact resistant, UV stabilized polycarbonate lens and molded gasket with stainless steel screws.



SPECIFICATIONS

Input Power	120/277 VAC; 24 VDC remote
Operating Temp	-20 °C – 50 °C
Housing	Fiberglass reinforced polycarbonate
Warranty	Five year warranty
Listed to UL 924, NFPA 101; WET	

SELF-DIAGNOSTIC

UL 924 LISTED

ORDERING INFORMATION

Series	Faces	Letter	Voltage	Wattage	Housing
FRO	1 – Single ¹	R – Red	6 – 6 volts	12 – 12 watts	G – Gray
	2 – Double ²	G – Green	12 – 12 volts	15 – 15 watts	

Ordering Example: FRO-1-R-6-12-G

Options: SDT Self-Diagnostics · CW Cold Weather · TP Tamper-Proof · NH No Heads

¹ Single faces available only in 15W models. ² Double faces available only in 12W models.

LISTED TO



UL 924 / NFPA 101

“Engineered for the spaces it protects.”