

· TYPE _____ · DATE _____ · PROJECT _____

EXIT + EMERGENCY
Both in one unit

REDUCED PROFILE
Slim on the wall

SAGE LIVE™
Monitored on the central battery

DAMP RATED
Wet/damp location listed

Harbor

HAR

GENERAL DESCRIPTION

A reduced-profile all-LED exit and emergency thermoplastic combo. As part of the Sage central battery system, it's monitored continuously through Sage Live.

CONSTRUCTION & OPERATION

Ultra-bright, energy efficient, long-life Red or Green LED EXIT sign illumination.

Ultra-bright, energy efficient, long-life White LED adjustable LED lamp heads provide up to 30-ft center-to-center spacing with 3-ft path of egress at 10-ft mounting height.

1.5 watt (3 LEDs x 0.50 watt) per head.

Unique all-inclusive lamp, reflector and lens assembly.



SPECIFICATIONS

Input Power	Dual 120/277 VAC input
Operating Temp	0 °C to 50 °C
Housing	Injection-molded, engineering grade
Listed to UL 924, NFPA 101; cULus; DAMP	

DAMP RATED

SELF-DIAGNOSTIC

ORDERING INFORMATION

Series	Letter	Housing
HAR	R – Red	W – White
	G – Green	B – Black

Ordering Example: HAR-R-W

Options: RC Remote Capacity · SDT Self-Diagnostics · USA Assembled in USA

LISTED TO



UL 924 / NFPA 101

ASSEMBLED IN USA



Per Buy American Act

“Engineered for the spaces it protects.”