

TYPE _____ · DATE _____ · PROJECT _____

 CB COMPATIBLE Factory ELC for central battery	 SELECTABLE CCT 4000K or 5000K field selectable	 OCCUPANCY SENSOR PIR or microwave option	 LONG LIFE L70 > 190,000 hours
---	--	--	---

Hawthorne

HAW

GENERAL DESCRIPTION

Slim surface-mounted LED strip in steel housing. Available in 4ft and 8ft with selectable 5,000 or 10,000 lumen output. Optional factory-installed ELC connects to Sage central battery for full emergency code compliance..

CONSTRUCTION & OPERATION

Steel housing with PMMA lens in 4ft and 8ft lengths.

Selectable 5,000 or 10,000 lumen output with 4000K/5000K CCT.

Universal 120-277VAC with 0-10V dimming.


Optional occupancy sensor (PIR or microwave).

Factory-installed ELC available for Sage central battery emergency operation.

cULus damp location listed.

L70 > 190,000 hours.

DLC listed.



SPECIFICATIONS	
Lengths	4ft / 8ft
Lumen Output	5L: 5,000 lm 10L: 10,000 lm
CCT	4000K / 5000K (selectable)
Input	120-277 VAC
Dimming	0-10V standard
Listings	cULus / DLC / Damp
<div style="display: flex; justify-content: space-around;"> CB COMPATIBLE SAGE LIVE™ READY </div>	

ORDERING INFORMATION

Series	Watts	Volts	CODE	OPTION / DESCRIPTION
HAW	5L / 10L	MV 120/277VAC	4FT	4ft Length
			8FT	8ft Length
			SLSK	Selectable CCT 4000K/5000K
			OS	Occupancy Sensor — PIR
			ODS	Occupancy Sensor — Microwave
			ELCP2XX	Emergency Lighting Control
			EMXX	Emergency Driver
			WG	Wire Guard

Ordering Example: **HAW-10L-MV-4FT-SLSK-ELCP2XX**

CONFORMS TO JUL 924 / CSA C22.2 #141	ASSEMBLED IN USA Per Buy American Act
--	---

“Engineered for the spaces it protects.”