

TYPE _____ · DATE _____ · PROJECT _____

CB COMPATIBLE
 24 VDC remote (RE)

UNIVERSAL MOUNT
 Top · wall · pendant

DUAL FUNCTION
 Emergency + night / security

SELECTABLE CCT
 2700–5000 K · CRI 90

Ignite

IGN

GENERAL DESCRIPTION

Universal-mount LED emergency downlight with a 4" trim — top, wall, or pendant mount. An efficient, inconspicuous emergency luminaire that blends with general lighting in long corridors. Die-cast housing, baked-enamel finish. Dual-function: emergency plus night / security lighting. Field-selectable CCT, dimmable to 10%. Operates remote from the central battery (24 VDC, RE) or on line voltage (AC).

CONSTRUCTION & OPERATION

Die-cast lamp housing, baked-enamel finish, stainless hardware; 4" trim.

Universal mount: top, wall, or pendant (length to spec).

Field-selectable CCT 2700–5000 K; CRI > 90; RE = 5000 K.

Universal 120/277 VAC; PF > 0.90; dimmable to 10% (AC only).

AC, or RE — 24 VDC remote from central battery; ≥ 90 min on loss of AC.

> 50,000 h lamp life (L70); 5-year warranty.



SPECIFICATIONS

Emergency Output	1100 lm @ 12 W (4")
Color Temp	2700/3000/4000/5000 K · RE 5000 K
CRI	> 90
Mounting	Top · wall · pendant
Input	120/277 VAC (AC) · 24 VDC (RE)
Lamp Life	> 50,000 h (L70) · PF > 0.90
Listed to UL 924 / NFPA 101 · ETL damp location · Energy Star · RoHS	

UL 924 LISTED

ETL DAMP LOCATION

ORDERING INFORMATION

Series	Lens	Lumens	Operation	CCT	Options
IGN	4 4"	11L 1100 lm	AC 120/277 V	SK 2700 K	NOR Security / ASA
			RE 24 V · CB	3000 K	PENX Pendant (X=len)
				4000 K	W Wall mount
				5000 K	

Ordering Example: IGN-4-11L-AC-SK-PEN12

Selectable CCT: AC only · RE = 5000 K
 NOR = normally-on (DC option: RE)

CONFORMS TO


UL 924 / NFPA 101

ASSEMBLED IN USA


Per Buy American Act

“Engineered for the spaces it protects.”