

· TYPE _____ · DATE _____ · PROJECT _____

SWING FACE
180° max swing, hang-straight hinge

UNIVERSAL MOUNT
Field-set wall or ceiling

SELF-TEST
Diagnostics standard (BB models)

cETLus LISTED
Tested to UL 924 / NFPA 101

Jasmine

JAS

GENERAL DESCRIPTION

A contemporary center-lens luminaire delivering a soft natural glow with even illumination and minimized glare.

CONSTRUCTION & OPERATION

Emergency lighting from 1,250 Lm to 2,100 Lm with adjustable Sage Relay, powered from a low-voltage central battery system. See Page 2 for details.

Available with factory-installed UL Listed Sage Relay, for connection to a central battery system, DC emergency power output.

Available in 3500K (warm natural white), 4000K (neutral white) & 5000K (cool white) color temperatures.*

Long life LEDs provide at least 180,000 hours of operation with at least 70% of initial lumen output (L70) and 54,000 hours with at least 90% of initial lumen output (L90).**



SPECIFICATIONS

Operation	AC · RE
LED Life	180,000 hours
Operating Temp	-25 °C to 50 °C

Listed to cULus; DAMP; DLC Premium

DAMP RATED

cULus LISTED

ORDERING INFORMATION

Series	Size	Nominal Lumens (Sl, Selectable)	Color Temp (Sk, Selectable)	Operation
JAS	22 – 2' x 2'	SL	SK	AC – 120–277VAC
	24 – 2' x 4'			RE – 24V Remote from central battery

Ordering Example: JAS-24-SL-SK-AC-RLY

Options: RLY Sage Relay · EMXX Emergency Driver · ODS Occupancy Sensor Microwave · SMKXX Surface Mount Kit · FLKXX Flange KIT · CMK Cable Mount Kit

1 See Electrical Data for specific values. 2 See Sage Relay details table, Page 2.

LISTED TO



“Engineered for the spaces it protects.”