

TYPE _____ · DATE _____ · PROJECT _____

 CB COMPATIBLE Remote central battery version	 ULTRA-LOW POWER ½ to 1 watt per sign	 SWING FACE Auto-returns after impact	 CUSTOM GRAPHICS Colors and lettering available
--	--	--	--

Jasper

JAS

GENERAL DESCRIPTION

Premium crystal edge-lit exit sign with swing-face aluminum housing. Diamond-polished lenses and four LEDs per face for exceptional brightness and ultra-low power. CB compatible remote versions.

Custom graphics available.

CONSTRUCTION & OPERATION

Extruded aluminum with Hang Straight Hinge for 180° motion and auto-return.

1/4" impact-resistant acrylic lens with diamond-polished optics.

Four LEDs per face for ultra-low power (½W to 1W).

Universal 120/277VAC.

Remote versions connect to Sage central battery.

Custom graphics and colors available.

UL 924 listed.



SPECIFICATIONS	
Power	½ to 1 watt per sign
LEDs	4 per face
Lens	1/4" acrylic, diamond-polished
Hinge	Hang Straight — 180° range
Input	120/277 VAC
Listings	UL 924 / NFPA 101
<div style="display: flex; justify-content: space-around;"> CB COMPATIBLE SAGE LIVE™ READY </div>	

ORDERING INFORMATION

Series	Watts	Volts	CODE	OPTION / DESCRIPTION
CRSW	BB	120/277VAC	RE	Remote — Central Battery
			W	White Housing
			BRZ	Bronze Housing
			SLV	Silver Housing
			CUSTOM	Custom Graphics

Ordering Example: **CRSW-BB-120-W**

CONFORMS TO UL 924 / CSA C22.2 #141	ASSEMBLED IN USA Per Buy American Act
---	---

“Engineered for the spaces it protects.”