

· TYPE _____ · DATE _____ · PROJECT _____

FIELD-ADJUSTABLE
Wall or ceiling, set on site

EDGE-LIT
Uniform acrylic panel

SURFACE MOUNT
No recess required

DAMP RATED
Wet/damp location listed

Jasper

JSP

GENERAL DESCRIPTION

A surface-mount edge-lit exit sign, field-adjustable for wall or ceiling mount, with a high-grade acrylic panel and directional graphics. Clean, bright, and flexible on site.


CONSTRUCTION & OPERATION

Extruded aluminum LED lamp housing mounts to a form-fitting canopy in solid aluminum which is field adjustable for wall or ceiling mount.

Standard finishes: Satin white enamel and brushed aluminum. Optional finishes: Painted colors in any custom shade, or anodized finishes in satin bronze, polished gold, mirror silver & many others.

Diamond polished acrylic lenses for optimum light transmission, exterior quality and high brightness.

Ultra high output LEDs with up to 5 candela output in green or red produce brilliant graphic illumination well above code minimums.



SPECIFICATIONS

Input Power	Universal 120/277 VAC
Operation	BB · NB · REC · REP · REM
Brightness	6 ft-Lambert (21 cd/m²)
Uniformity	Better than 4:1
LED Life	In excess of 20 years
Emergency	90 min for each sign
Operating Temp	0 °C to 50 °C
Listed to UL 924, NFPA 101; cETLus (Intertek); BABA; BAA; DAMP	

DAMP RATED

SELF-DIAGNOSTIC

ORDERING INFORMATION

Series	Operation	Faces	Letter	Backgrd	Trim	Arrow	Mount
JSP	BB – Battery Backup	1 – Single	R – Red	C – Clear	W – White	NA – None	TW – Universal
	NB – No Battery (AC)	2 – Double	G – Green	M – Mirror	K – Black	AB – Both	
	REC – Remote / Central			W – White	A – Alum	AR – Right	
	REP – Remote DC / POE			K – Black	B – Satin Bronze	AL – Left	
	REM – Remote (Master)			X – Custom	X – Custom	LR – Single	
						CX – Custom Graphics	

Ordering Example: JSP-BB-1-R-C-B-NA-TW-DG

Options: DG Auto Battery Diagnostics · DP Damp Location · DAC120 Dual AC Input (120 VAC) · DAC277 Dual AC Input (277 VAC) · 48 48VDC input (REP Models) · 60 60VDC input (REP Models)

SF = single face, DF = double face (per the Arrow Direction column). Arrow AR/AL apply to single-face signs; LR applies to double-face signs.

LISTED TO



UL 924 / NFPA 101

ASSEMBLED IN USA



Per Buy American Act

“Engineered for the spaces it protects.”