

· TYPE _____ · DATE _____ · PROJECT _____

VAPOR-TIGHT
Sealed enclosure

FIELD-SELECTABLE
Lumen & Kelvin

SENSOR-READY
Controls-ready

5-YEAR WARRANTY
Total customer satisfaction

Juniper

JUN

GENERAL DESCRIPTION

A vapor-tight, sensor-ready LED luminaire with field-selectable lumen output and CCT — sealed for car washes, parking, food processing, and damp environments.

CONSTRUCTION & OPERATION

Emergency lighting with adjustable Sage Relay, powered from a low-voltage central battery system.

Available with factory-installed UL Listed Sage Relay, for connection to a central battery, DC emergency power system.

Polycarbonate lens.

Light gray polycarbonate housing with stainless steel latches.



SPECIFICATIONS

Input Power	Universal 120-277V AC (50-60Hz) is
LED Life	178,000 hours
Operating Temp	-40 °C to 43 °C
Warranty	5 year warranty
Listed to cULus (Wet); DLC Premium	

cULus WET LISTED

DLC PREMIUM

ORDERING INFORMATION

Series	Size	Lumens	CCT
JUN	7L	SL – 7,000 / 6,000 / 5,000 lm	SK – 3500K / 4000K / 5000K

Ordering Example: JUN-7L-SL-SK-RLY

Options: RLY Sage Relay · EM10 10W Emergency driver · EM13 13W Emergency driver · NSF NSF Certified

Nominal values: see Electrical data for specific values. See Sage Relay Power details table, Page 2.

LISTED TO



“Engineered for the spaces it protects.”