

· TYPE _____ · DATE _____ · PROJECT _____

HIGH POWER
Greater output and reach

POLYCARBONATE
Impact-resistant housing

CENTRAL-BATTERY
Low-voltage powered

DAMP RATED
Wet/damp location listed

LightHouse

LIG

GENERAL DESCRIPTION

A high-power indoor polycarbonate LED remote head with adjustable lamp heads, powered from the central battery over low-voltage wiring.

CONSTRUCTION & OPERATION

Ultra-bright, energy efficient, long-life White LED adjustable lamp heads provide up to 100-ft center-to-center spacing with a 6-ft path of egress at 15-ft mounting height.

6.0 watt (12 LEDs x 0.50 watt) per head.

Adjustable glare-free PAR-Type lamp heads with allinclusive lamp, reflector and lens assembly.

Powered from low voltage power source with low voltage wiring (not provided).



SPECIFICATIONS

Input Power	120/277 VAC; 24 VDC remote
Operation	RB · RE
Operating Temp	0 °C to 50 °C
Warranty	5 year warranty

Listed to UL 924, NFPA 101; DAMP

DAMP RATED

UL 924 LISTED

ORDERING INFORMATION

Series	Operation	Lamp Heads	Housing
LIG	RB – Powered from EBU or EXIT Combo	1 – Single Head	(Blank) – White
	RE – Powered from Central Battery System	2 – Double Head	B – Black

Ordering Example: LIG-RB-1-B

LISTED TO



UL 924 / NFPA 101

“Engineered for the spaces it protects.”