

· TYPE _____ · DATE _____ · PROJECT _____

EXIT + EMERGENCY
One combined unit

ADJUSTABLE HEADS
Aim the egress light

CHICAGO-APPROVED
Meets the jurisdiction

DAMP RATED
Wet/damp location listed

Linden

LIN

GENERAL DESCRIPTION

A white-LED combination exit sign and emergency lighting unit in a steel housing, Chicago/regionally approved — single or double face, with two integral adjustable LED heads.

CONSTRUCTION & OPERATION

Long lasting, energy efficient white LED exit sign illumination.

Single or double face configuration.

Two 6V 5.3W adjustable white LED lamp heads.

Durable 20-gauge steel construction.



SPECIFICATIONS

Input Power	MV
Operating Temp	0 °C to 50 °C
Housing	Durable 20-gauge steel construction
Warranty	Five year warranty
Listed to UL 924, NFPA 101; DAMP	

DAMP RATED

UL 924 LISTED

ORDERING INFORMATION

Series	Faces	Letter	Housing	Directional Arrow
LIN	1 – Single Face	R – Red	W – White	NA – Exit None
	2 – Universal Single/Double Face		B – Black	DA – Exit Double
				RA – Exit Right
				LA – Exit Left
				LARA – Exit Left/Right
				SW-LA – Stairs Left
				SW-NA – Stairs None
				SW-DA – Stairs Double
				SW-RA – Stairs Right
				SW-LARA – Stairs Left/Right

Ordering Example: LIN-1-R-W-NA

Options: RC Remote Capacity

1. Available in single face configuration only. 2. Available in double face configuration only.

LISTED TO
UL 924 / NFPA 101

“Engineered for the spaces it protects.”