

· TYPE _____ · DATE _____ · PROJECT _____

DIE-CAST PREMIUM
Heavy-grade housing

FIELD CHEVRONS
Direction set on site

DOUBLE-FACE
Convert in the field

DAMP RATED
Wet/damp location listed

Meridian

MER

GENERAL DESCRIPTION

A premium-grade die-cast aluminum exit sign with field-selectable knockout chevrons and double-face field conversion — flexible without a re-order.

CONSTRUCTION & OPERATION

Ultra bright, energy efficient, long life Red or Green LEDs.

Premium-grade, die-cast aluminum housing (also available in optional black or white powder-coated finishes).

Field selectable knockout Chevron directional indicators.

Unique design allows double face conversion in the field.



SPECIFICATIONS

Input Power	120/277 VAC; 24 VDC remote
Operation	BB · AC · RE
Operating Temp	0 °C to 50 °C
Warranty	Five year warranty
Listed to UL 924, NFPA 101; DAMP	

DAMP RATED

SELF-DIAGNOSTIC

ORDERING INFORMATION

Series	Operation	Faces	Letter	Housing	Face Panel
MER	BB – Battery Backup	1 – Single Face	R – Red	A – Aluminum	A – Aluminum
	AC – AC Only	2 – Double	G – Green	W – White	W – White
	RE – Remote (central battery)	3 – Universal Single/Double		B – Black	B – Black

Ordering Example: MER-BB-3-R-A-A-SDT

Options: SDT Self-Diagnostics (footnote 1) · 2C-120 Dual Circuit with 120V input (footnote 2) · 2C-277 Dual Circuit with 277V input (footnote 2) · TP Tamper-Proof · USA Assembled In USA

1 = SDT (Self-Diagnostics): Available only with EM units. 2 = 2C-120 / 2C-277 (Dual Circuit): Available only with AC units.

LISTED TO



UL 924 / NFPA 101

ASSEMBLED IN USA



Per Buy American Act

“Engineered for the spaces it protects.”