

· TYPE _____ · DATE _____ · PROJECT _____

SELF-LUMINOUS
Tritium-lit, always on

ACCESSIBLE
Regionally-approved configs

NO TESTING
Legally exempt from monitoring

BAA CERTIFIED
Assembled in the USA

Mesa

MES

GENERAL DESCRIPTION

Self-luminous EXIT signs illuminated by sealed tritium gas — no power, no battery, legally exempt from monitoring and testing, and available in regionally-approved accessible-exit configurations.

CONSTRUCTION & OPERATION

Double-wall housing of extruded aluminum with minimum wall thickness of .09" (2.3 mm). No visible mounting hardware.

Standard finish: satin anodized brushed aluminum; optional finishes available in painted enamel color.

Polycarbonate faceplate window of .125" (3 mm) minimum thickness.

Universal field-adjustable chevron arrows and universal mounting brackets.



SPECIFICATIONS

Input Power 120/277 VAC; 24 VDC remote

Operating Temp 0 °C to 50 °C

Listed to UL 924, NFPA 101; cETLus (Intertek)

UL 924 LISTED

NO LOAD

ORDERING INFORMATION

Series	Useful Life	Faces	Face Color	Housing
MES	10 – 10 YRS	1 – single	R – RED	BA – BRUSHED ALUMINUM
	20 – 20 YRS	2 – double	G – GREEN	

Ordering Example: MES-10-1-R-BA

LISTED TO



UL 924 / NFPA 101

ASSEMBLED IN USA



Per Buy American Act

“Engineered for the spaces it protects.”