

· TYPE _____ · DATE _____ · PROJECT _____

MR16 OPTICS
Crisp, focused beams

ADJUSTABLE HEADS
Aim the light

CENTRAL-BATTERY
Low-voltage powered

DAMP RATED
Wet/damp location listed

Mist

MIS

GENERAL DESCRIPTION

An indoor high-performance MR16 LED remote head with adjustable heads, powered from the central battery over low-voltage wiring.

CONSTRUCTION & OPERATION

Long lasting, efficient ultra bright white LED lamp heads.

Adjustable 3.6W lamp heads increase center-to-center spacing.

Powered from low voltage power source with low voltage wiring (not provided).

Injection-molded, engineering grade, 5VA flame retardant, high-impact resistant, thermoplastic in white finish.



SPECIFICATIONS

Input Power	120/277 VAC; 24 VDC remote
Operation	RB · RE
Operating Temp	0 °C to 50 °C
Warranty	5 year warranty

Listed to UL 924, NFPA 101; DAMP

DAMP RATED

UL 924 LISTED

ORDERING INFORMATION

Series	Operation	Lamp Heads	Housing
MIS	RB – Powered from EBU or EXIT Combo	1 – Single Head	(Blank) – White
	RE – Powered from Central Battery System	2 – Double Head	

Ordering Example: MIS-RB-2-HL

Options: (Blank) 3 · HL 7

LISTED TO



UL 924 / NFPA 101

“Engineered for the spaces it protects.”