

· TYPE _____ · DATE _____ · PROJECT _____

LOW PROFILE
Barely projects

THERMOPLASTIC
Light, durable

INTEGRAL BATTERY
90-minute egress

DAMP RATED
Wet/damp location listed

Orbit

ORB

GENERAL DESCRIPTION

A reduced-profile thermoplastic LED emergency unit with an integral battery — discreet egress lighting that barely projects from the wall.

CONSTRUCTION & OPERATION

Ultra-bright, energy efficient, long-life White LED adjustable lamp heads provide up to 30-ft center-to-center spacing with 3-ft path of egress at 10-ft mounting height.

1.5 watt (3 LEDs x 0.50 watt) per head.

Unique all-inclusive lamp, reflector and lens assembly.

Dual 120/277 voltage standard. Optional dual 120/230 voltage available.



SPECIFICATIONS

Input Power	Dual 120/277 VAC standard; optional
Operation	BB
Operating Temp	0 °C to 50 °C
Housing	Injection-molded, engineering grade
Warranty	5 year warranty
Listed to UL 924, NFPA 101; cULus; DAMP	

DAMP RATED

UL 924 LISTED

ORDERING INFORMATION

Series	Operation	Housing
ORB	BB – Battery Backup	W – White
		B – Black

Ordering Example: ORB-BB-B-RC

Options: RC Remote Capacity · SDT Self-Diagnostics · USA Assembled in USA · NH No Heads

LISTED TO



UL 924 / NFPA 101

ASSEMBLED IN USA



Per Buy American Act

“Engineered for the spaces it protects.”