

TYPE _____ · DATE _____ · PROJECT _____

HIGH OUTPUT
6,000+ lm for large volumes

CB COMPATIBLE
Central battery operation

IP67 RATED
Watertight polycarbonate lens

DUAL FUNCTION
Emergency + night/security

Orion

ORI

GENERAL DESCRIPTION

High-output emergency luminaire producing over 6,000 lumens for warehouses, hangars, and large commercial spaces. Ceiling heights to 40ft+. IP67 polycarbonate lens.

Recessed or surface mount. Central battery compatible. UL 924 listed.

CONSTRUCTION & OPERATION

IP67 UV-stabilized polycarbonate lens with watertight seal.

Recessed machined aluminum faceplate or surface-mount steel housing.


Central battery compatible for low-voltage normal and emergency operation.

Lamps in parallel for redundancy.

4,700K CCT, CRI 70, L70 at 50,000 hours.

Dual emergency/night-security function.

UL 924 listed.



SPECIFICATIONS

Lumen Output	> 6,000 lm
CCT / CRI	4,700K / CRI 70
Ceiling Height	10 to 40+ feet
IP Rating	IP67
Lamp Life	L70 at 50,000 hours
Listings	UL 924 / NFPA 101

CB COMPATIBLE	SAGE LIVE™ READY
----------------------	-------------------------

ORDERING INFORMATION

Series	Watts	Volts	CODE	OPTION / DESCRIPTION
ORI	50-150W	120/277VAC	BB	Integral Battery Unit
		24VDC	RE	Remote — Central Battery
			WAL	Wide Angle Lens

Ordering Example: **ORI-RE-24**



“Engineered for the spaces it protects.”