

· TYPE _____ · DATE _____ · PROJECT _____

MR16 OPTICS
Focused beams

SEMI-RECESSED
Low profile

INTEGRAL BATTERY
90-minute egress

DAMP RATED
Wet/damp location listed

Peak

PEA

GENERAL DESCRIPTION

A semi-recessed LED MR16 emergency unit with an integral battery — focused egress light in a low-profile recessed form.

CONSTRUCTION & OPERATION

Two fully adjustable semi-recessed, round 7-watts LED MR16 lamp heads for optimal light distribution.

Ultra-bright, energy efficient, long-life White LED lamps provide up to 76-ft center-to-center spacing with 3-ft path of egress at 7.5-ft mounting height.

Injection-molded, engineering grade, 5VA flame retardant, high-impact resistant, thermoplastic in white or black finish.



SPECIFICATIONS

Input Power	120/277 VAC; 24 VDC remote
Operation	BB
Operating Temp	0 °C to 50 °C
Warranty	5 year warranty

Listed to UL 924, NFPA 101; DAMP

DAMP RATED

SELF-DIAGNOSTIC

ORDERING INFORMATION

Series	Operation	Housing
PEA	BB – Battery Backup	(Blank) – White
		B – Black

Ordering Example: PEA-BB-B-USA

Options: USA Assembled in USA · Self-diagnostics Self-diagnostics

LISTED TO



ASSEMBLED IN USA



“Engineered for the spaces it protects.”