

· TYPE _____ · DATE _____ · PROJECT _____

STAIRWELL-READY
Egress stairs

LENSED
Uniform output

FIELD-SELECTABLE
Lumen & Kelvin

DAMP RATED
Wet/damp location listed

Pinnacle

PIN

GENERAL DESCRIPTION

A premium lensed stairwell strip light with field-selectable lumen output and CCT — uniform, durable lighting for egress stairs.

CONSTRUCTION & OPERATION

Emergency lighting with adjustable Sage Relay, powered from a low-voltage central battery system.

Available with factory-installed UL Listed Sage Relay, for connection to a central battery, DC emergency power system.

Field selectable 3500K (warm/neutral white), 4000K (neutral white), and 5000K (cool white) color temperatures.

Long-life LEDs provide 190,000 hours of operation with at least 70% of initial lumen output (L70), and 58,000 hours with at least 90% of initial lumen output (L90).



SPECIFICATIONS

Light Output	Emergency lumens are calculated based
LED Life	190,000 hours
Operating Temp	0 °C to 50 °C
Warranty	5 year warranty
Listed to UL 924, NFPA 101; cULus; DAMP; DLC Premium	

DAMP RATED

UL 924 LISTED

ORDERING INFORMATION

Series	Size	Lumens	CCT	Voltage
PIN	4 – 4FT	SL – (4FT): 4,200lm / 4,800lm / 6,000lm	SK – 3500K / 4000K / 5000K	MV – 120-277VAC
	2 – 2FT	SL – (2FT): 2,100lm / 2,700lm / 3,300lm		

Ordering Example: PIN-4-SL-SK-MV-ODS

Options: RLY Sage Relay ("XX" = varies with fixture size and power; see Options table for complete part number; see Sage Relay Power details table, Page 2) · EM Emergency driver (see option table on page 2) · ODS Occupancy Dimming Sensor

Nominal values; see Electrical data for specific values. Sage Relay: see Sage Relay Power details table, Page 2.

LISTED TO



“Engineered for the spaces it protects.”