

· TYPE _____ · DATE _____ · PROJECT _____

NYC-COMPLIANT
Meets New York City

RECESSED
Flush to the ceiling

EDGE-LIT ALUMINUM
Uniform, durable

DAMP RATED
Wet/damp location listed

Ridge

RDG

GENERAL DESCRIPTION

A New York City-compliant recessed edge-lit aluminum exit sign — flush-mounted, durable, and evenly illuminated.

CONSTRUCTION & OPERATION

Ultra bright, energy efficient, long life Red LED exit sign illumination.

UV-stabilized ultra-clear acrylic edgelit panel provides consistent, uniform illumination.

Double face utilizes factory installed silver or white mylar background panel.

New York City compliant 8" EXIT letters.



SPECIFICATIONS

Input Power	Dual 120/277 VAC standard (voltage)
Operation	BB · NB · REC · REP
Emergency	Minimum 90-minute emergency
Operating Temp	0 °C – 50 °C
Warranty	Five year warranty
Listed to UL 924, NFPA 101; cETLus (Intertek); DAMP	

DAMP RATED

SELF-DIAGNOSTIC

ORDERING INFORMATION

Series	Operation	Faces	Letter	Panel	Trim Plate
RDG	BB – Battery Backup	1 – Single Face	R – Red	C – Clear	W – White
	NB – No Battery (AC)	2 – Double Face		M – Mirror	B – Black
	REC – Remote / Central			W – White	A – Aluminum
	REP – Remote DC / POE				

Ordering Example: RDG-BB-1-R-C-A-SDT

Options: SDT Self-Diagnostics · WM Wall Mount

LISTED TO



UL 924 / NFPA 101

“Engineered for the spaces it protects.”