

TYPE _____ · DATE _____ · PROJECT _____

CB COMPATIBLE
Factory ELC for central battery

SELECTABLE CCT
Warm, neutral, or cool white

RETROFIT READY
New construction or retrofit

0-10V DIMMING
Standard dimming compatibility

Reed

REE

GENERAL DESCRIPTION

4ft and 8ft surface-mounted LED strip with selectable lumen output and CCT. Steel housing for commercial and institutional spaces. Optional factory-installed ELC connects to Sage central battery for emergency compliance..

CONSTRUCTION & OPERATION

Steel housing in 4ft and 8ft.


Selectable lumen output and CCT.

Universal 120-277VAC with 0-10V dimming.

Factory-installed ELC available for Sage central battery emergency operation.

cULus listed.

New construction or retrofit installation.



SPECIFICATIONS	
Lengths	4ft / 8ft
Lumen Output	Selectable
CCT	Selectable
Input	120-277 VAC
Dimming	0-10V standard
Listings	cULus / DLC
<div style="display: flex; justify-content: space-around;"> CB COMPATIBLE SAGE LIVE™ READY </div>	

ORDERING INFORMATION

Series	Watts	Volts	CODE	OPTION / DESCRIPTION
SLL	25-50W	120-277VAC	4FT	4ft Length
			8FT	8ft Length
			ELCXX	Emergency Lighting Control

Ordering Example: **SLL-4FT-120-ELCXX**



“Engineered for the spaces it protects.”