

· TYPE _____ · DATE _____ · PROJECT _____

EXIT + EMERGENCY
Both in one unit

LOW LEVEL
Floor-line mounting

ALL LED
Efficient, long-life

DAMP RATED
Wet/damp location listed

Ridgeline

RID

GENERAL DESCRIPTION

A low-level all-LED thermoplastic exit and emergency combo with a single-face EXIT — code-compliant low-mount egress marking.

CONSTRUCTION & OPERATION

Long lasting, efficient ultra bright white LED light strip.

3.1 watts (24 LEDs x 0.13 watts) per light strip.

High performance, smooth, chrome plated, metallized reflector with acrylic UV stabilized lens for optimal light distribution.

Long life ultra-bright, energy efficient Red or Green LED EXIT sign illumination



SPECIFICATIONS

Input Power	120/277 VAC; 24 VDC remote
Operating Temp	0 °C – 50 °C
Housing	Patented specification-grade, low
Warranty	Five year warranty
Listed to UL 924, NFPA 101; DAMP	

DAMP RATED

UL 924 LISTED

ORDERING INFORMATION

Series	Faces	Letter	Housing
RID	1 – Single Face	R – Red	W – White
		G – Green	B – Black

Ordering Example: RID-1-R-W

LISTED TO



UL 924 / NFPA 101

“Engineered for the spaces it protects.”