

TYPE \_\_\_\_\_ · DATE \_\_\_\_\_ · PROJECT \_\_\_\_\_

**CB COMPATIBLE**  
24VDC central battery operation

**MODERN DESIGN**  
Soft corner contemporary styling

**UNIVERSAL FACE**  
Single or double, field set

**SELF-DIAGNOSTICS**  
Optional SDT auto-test

# Rowan

ROW

## GENERAL DESCRIPTION

Contemporary soft-corner LED exit sign in thermoplastic. Universal single/double face. 120/277VAC with integral battery or 24VDC central battery operation.

Optional self-diagnostics. Modern design for commercial and hospitality applications.

## CONSTRUCTION & OPERATION

Engineering grade thermoplastic with contemporary soft corner styling.

Universal single/double face with field selectable chevrons.


Snap-together install.

Universal 120/277VAC with 4.8V NiCd battery, 90-minute minimum.

24VDC central battery or 60VDC POE operation.

Optional SDT diagnostics.

UL 924, NFPA 101, Title 20 listed.



### SPECIFICATIONS

<b>Input</b>	120/277 VAC (Universal)
<b>Battery</b>	4.8V NiCd, maintenance-free
<b>Duration</b>	90 min. minimum
<b>DC Operation</b>	24VDC (CB) / 60VDC (POE)
<b>Face Config.</b>	Universal Single/Double
<b>Listings</b>	UL 924 / NFPA 101 / Title 20

CB COMPATIBLE

SAGE LIVE™ READY

## ORDERING INFORMATION

Series	Watts	Volts	CODE	OPTION / DESCRIPTION
BLD	BB	120/277VAC	RE	Remote — Central Battery
			W	White Housing
			B	Black Housing
			R	Red Letter Color
			G	Green Letter Color
			SDT	Self-Diagnostics
			2C	Dual Circuit

Ordering Example: **BLD-BB-120-R-W**



“Engineered for the spaces it protects.”