

· TYPE _____ · DATE _____ · PROJECT _____

BACK-LIT
Even, low glare

FIELD-SELECTABLE
Lumen & Kelvin

FLAT PANEL
Clean ceiling

DAMP RATED
Wet/damp location listed

Sage

SAG

GENERAL DESCRIPTION

A back-lit LED flat panel with field-selectable lumen output and CCT — even, low-glare ceiling light for offices, schools, and healthcare.


CONSTRUCTION & OPERATION

Emergency lighting with adjustable Sage Relay, powered from a low-voltage central battery system.

Available with factory-installed UL Listed Sage Relay, for connection to a central battery, DC emergency power system.

Field selectable 3500K (warm/neutral white), 4000K (neutral white), and 5000K (cool white) color temperatures.*

Long-life LEDs provide 144,000 hours of operation with at least 70% of initial lumen output (L70), and 44,000 hours with at least 90% of initial lumen output (L90).**



SPECIFICATIONS

Light Output	Lumens = Emergency Power Rating
LED Life	144,000 hours
Operating Temp	0 °C to 50 °C
Warranty	5 year warranty
Listed to cULus; DAMP; DLC Premium	

DAMP RATED

cULus LISTED

ORDERING INFORMATION

Series	Lumens	CCT	Voltage
SAG	SL – Nominal lumens (sel.)	SK – 3500K; 4000K; 5000K	MV – 120-277VAC
Ordering Example: SAG-SL-SK-MV			

Options: RLY Sage Relay. "XX" = Varies with fixture size and power; see Options table for complete part number. (See Sage Relay Power details table, page 2.) · EMXX Emergency driver; see option table on page 2. · DWS Dimmer Switch; see option table on page 2.

1 Nominal values, see Electrical data for specific values. 2 See Sage Relay Power details table, Page 2.

LISTED TO



“Engineered for the spaces it protects.”