

· TYPE _____ · DATE _____ · PROJECT _____

LOW PROFILE
Discreet

THERMOPLASTIC
Light, durable

INTEGRAL BATTERY
90-minute egress

DAMP RATED
Wet/damp location listed

Sentinel

SEN

GENERAL DESCRIPTION

A low-profile thermoplastic LED emergency unit with an integral battery — clean, unobtrusive egress lighting.

CONSTRUCTION & OPERATION

Adjustable long lasting, efficient, ultra bright white LED lamp heads.

One, 0.5W white LED per lamp head.

Unique all-inclusive lamp, reflector and lens assembly.

Injection-molded, engineering grade, 5VA flame retardant, high-impact resistant, thermoplastic in white or black finish.



SPECIFICATIONS

Input Power	120/277 VAC; 24 VDC remote
Operating Temp	0 °C – 30 °C
Housing	Injection-molded, engineering grade
Warranty	Five year warranty
Listed to UL 924, NFPA 101; DAMP	

DAMP RATED

UL 924 LISTED

ORDERING INFORMATION

Series	Housing
SEN	(blank) – White
	B – Black

Ordering Example: SEN-B

Options: RC Remote Capacity¹ · SPV 120/230 Volt 50/60Hz · HL High Lumen LED¹

LISTED TO



UL 924 / NFPA 101

“Engineered for the spaces it protects.”