

· TYPE _____ · DATE _____ · PROJECT _____

90° ADJUSTABLE
Aim the pattern

OUTDOOR AREA
Parking and perimeter

OPTIONAL EMERGENCY
Egress-ready

Spark

SPA

GENERAL DESCRIPTION

A high-quality outdoor area light, adjustable through 90 degrees to optimize the lighting pattern, with an optional emergency configuration.

CONSTRUCTION & OPERATION

Emergency lighting with adjustable Sage Relay, powered from a low-voltage central battery system.

Available with factory-installed UL Listed Sage Relay, for connection to a central battery, DC emergency power system.

Field Selectable 3000K, 4000K and 5000K color temperatures.

Long-life LEDs provide 167,000 hours of operation with at least 70% of initial lumen output (L70), and 51,000 hours with at least 90% of initial lumen output (L90).



SPECIFICATIONS

Light Output	6,002
LED Life	167,000 hours
Operating Temp	0 °C to 50 °C

Listed to cULus (Wet); DLC Premium; IP65

cULus WET LISTED

DLC PREMIUM

ORDERING INFORMATION

Series	Size	Nominal Lumens (SL, Selectable ²)	Color Temp (SK, Selectable ²)	Voltage
SPA	6L – 6,000L	6L: SL – 3000lm / 4000lm / 5000lm / 6000lm	SK – 3000K / 4000K / 5000K	MV – 120-277VAC
	12L – 12,000L	12L: SL – 6000lm / 8000lm / 10000lm / 12000lm		

Ordering Example: SPA-12L-SLSK-MV-RLY

Options: RLY Sage Relay

¹ See Sage Relay details table, Page 2. ² Nominal values. See Electrical Data for specific values.

LISTED TO



“Engineered for the spaces it protects.”