

· TYPE _____ · DATE _____ · PROJECT _____

NYC-COMPLIANT
Meets New York City

8" LETTERS
High-visibility EXIT

EDGE-LIT ALUMINUM
Clear panel, solid housing

DAMP RATED
Wet/damp location listed

Strata

STR

GENERAL DESCRIPTION

A red-LED surface-mount edge-lit aluminum exit sign, NYC-compliant, with an ultra-clear acrylic panel and 8-inch EXIT letters; double-face capable.

CONSTRUCTION & OPERATION

Ultra bright, energy efficient, long life Red LED exit sign illumination.

UV-stabilized ultra-clear acrylic edgelit panel provides consistent, uniform illumination.

Double face utilizes factory installed silver or white mylar background panel.

New York City compliant 8" EXIT letters.



SPECIFICATIONS

Input Power	Dual 120/277 voltage standard
Operation	BB · NB · REC · REP
Operating Temp	0 °C to 50 °C
Warranty	Five year warranty
Listed to UL 924, NFPA 101; cETLus (Intertek); DAMP	

DAMP RATED

SELF-DIAGNOSTIC

ORDERING INFORMATION

Series	Operation	Faces	Letter	Panel	Housing
STR	BB – Battery Backup	1 – Single Face	R – Red	C – Clear	W – White
	NB – No Battery (AC)	2 – Double Face		M – Mirror	B – Black
	REC – Remote / Central			W – White	A – Aluminum
	REP – Remote DC / POE				

Ordering Example: STR-BB-2-R-M-W-SDT

Options: SDT Self-Diagnostics · SPV 208/220/240 Volts, 50/60Hz

1 — With single face only. 2 — Available only with BB units.

LISTED TO



UL 924 / NFPA 101

“Engineered for the spaces it protects.”