

· TYPE _____ · DATE _____ · PROJECT _____

HAZ-LOC RATED
Classified areas

SEALED
Rated enclosure

INTEGRAL BATTERY
90-minute egress

SELF-TEST
Diagnostics on battery models

Summit

SUM

GENERAL DESCRIPTION

A hazardous-location LED emergency unit with an integral battery — sealed, rated egress lighting for classified areas.

CONSTRUCTION & OPERATION

Two fully adjustable, ultra bright 3.3 watt high performance MR-16 base LED lamp heads for optimized center-to-center spacing.

Housing is fiberglass reinforced polycarbonate construction in gray finish.

Corrosion-resistant enclosure with one piece, high-impact resistant, UV stabilized polycarbonate lens and molded gasket with stainless steel screws.



SPECIFICATIONS

Input Power	120/277 VAC; 24 VDC remote
Operating Temp	-20 °C – 50 °C
Housing	Fiberglass reinforced polycarbonate
Warranty	Five year warranty
Listed to UL 924, NFPA 101; WET	

SELF-DIAGNOSTIC

UL 924 LISTED

ORDERING INFORMATION

Series	Battery Voltage	Wattage	Housing
SUM	6 – 6 Volt	15 – 15 watts	G – Gray
	12 – 12 Volt		

Ordering Example: SUM-6-15-G

Options: SDT Self-Diagnostics · CW Cold Weather · TP Tamper-proof

LISTED TO



UL 924 / NFPA 101

“Engineered for the spaces it protects.”