

· TYPE _____ · DATE _____ · PROJECT _____

THIN PROFILE
Barely there on the wall

THERMOPLASTIC
Durable, lightweight

EFFICIENT LED
Long service life

DAMP RATED
Wet/damp location listed

Thermal

THE

GENERAL DESCRIPTION

A thin-profile thermoplastic exit sign — unobtrusive, efficient, and dependable for everyday egress.

CONSTRUCTION & OPERATION

Ultra bright, energy efficient, long life Red or Green LEDs.

Injection-molded, engineering grade, 5VA flame retardant, high-impact resistant, thermoplastic in white or black finish.

Specification-grade, low profile thin plastic design.

EZ snap-out Chevron directional indicators.



SPECIFICATIONS

Input Power	Universal Input 120/277VAC
Operation	BB · NB · REC · REP
Operating Temp	0 °C – 50 °C
Housing	Injection-molded, engineering grade
Warranty	Five year warranty
Listed to UL 924, NFPA 101; cETLus (Intertek); DAMP	

DAMP RATED

UL 924 LISTED

ORDERING INFORMATION

Series	Operation	No.Of Faces	Letter	Housing
THE	BB – Battery Backup	3 – Univ. Single/Double	R – Red	W – White
	NB – No Battery (AC)		G – Green	B – Black
	REC – Remote / Central			
	REP – Remote DC / POE			

Ordering Example: THE-BB-3-R-W

Options: 48 48 VDC Input* · 60 60 VDC Input*

*REP Operation. Spanish-language face plate option available — contact Sage.

LISTED TO



UL 924 / NFPA 101

“Engineered for the spaces it protects.”